





From the House of Bhuwalka Premier



Bhuwalka Premier Group of Companies

Bhuwalka Premier Group of Companies has been a leading supplier of TMT Steel for the Construction Industry in Karnataka since 1988.

At Bhuwalka Premier, we believe in perfection and have a strong team that works towards this endeavor guided by principles laid down by our founders.

We focus on the ease of business and aim at giving our customers unmatched service and developing long-term relationships with them.

Our biggest strength is the goodwill that we have developed over 25 years of experience working with the biggest and most reputed developers in the region

- Meenakshi Bright Steel Bars Pvt Ltd 75,000 MT's per annum of TMT Bars
- Deccan Alloys Pvt Ltd
 60,000 MT's per annum of rolled products
- Confab Steel Pvt Ltd (Sri Lanka)
 1,44,000 MT's per annum of TMT bars
- Bhuwalka Steel Industries Ltd (Sri Lanka)
 25,000 MT's per annum of billets and rolled products
- Bhuwalka Castings Pvt Ltd
 20,000 MT's per annum of castings
- Vishwakarma Refractories Pvt Ltd
 30,000 MT's per annum of refractories

Process

We use the latest Thermex Technology to manufacture the most reliable TMT bars. Thermex technology revolves around a precise, state-of-the-art Thermo-Mechanical -Treatment (TMT) developed and patented by Hennigsdorfer Stahl Engg. (HSE) Gmbh, Germany.



Thermex is the only rapid Water-quenching process that guarantees consistent properties over the entire bar length. The Thermex cooling technology involves subjecting the bar to a sophisticated hi-tech cooling process after rolling. This treatment converts the bar surface to a hardened structure. The subsequent phase involves cooling at ambient temperatures to allow the hot core to temper the surface through thermal exchange. This results in a unique structure characterized by tempered martensite in the peripheral zone and a fine grain ferrite-pearlite at the central zone.

Infrastructure



The rolling mills are High-speed mills with a slit rolling facility and built in environmen friendly reheatin furnaces with total automation to produce high quality TMT bars.

The roll turning facility is equipped with CNC machines for roll turning and groove cutting for perfect groove geometry.

We have unmatched infrastructure for testing raw materials and finished materials with sophisticated spectrometer and latest computer aided UTM for all qualities, sections and sizes of steel.



Quality

High standards of Inward Quality Control: The end product is only as good as the billets used. We use billets manufactured by us or sourced from leading manufacturers and subjected to highest standards of control.

Proper Controls are carried out on the entire TMT manufacturing process with testing at various stages of a globally proven advanced technology We follow a strict No Compromise Policy.

We are an approved manufacturer of Fe-500, Fe-500D, Fe-550 grade TMT Bars by the Bureau of Indian Standards (BIS) under license No. CM/L – 6974196 to IS 1786-2008.

Our Quality Management System has also been certified by Transpacific Certifications Limited and complies with the requirements of ISO 9001:2008 under certificate no 12097.

IS 1786-2008



M/L – 6974196

9001:2008

Specifications

		Steel - TMT Bars (order units - piece/bundle/tonne)									
	Size (mm)	No of rods in a bundle	No of Rods per MT	Length per rod(metres)	Nominal Weight (kg/m)	Range of weight for batch as per IS 1786:2008	Nominal Weight per 12 M rod	Range of Weight per 12 M rod as per IS 1786:2008	Nominal Weight per Bundle	Range Of Weight per Bundle as per IS:1786:2008	
	8	10	211	12	0.395	0.367 - 0.423	4.74	4.408 - 5.072	47.4	44.082 - 50.718	
	10	7	135	12	0.617	0.574 - 0.660	7.404	6.886 - 7.922	51.83	48.202 - 55.458	
	12	5	94	12	0.888	0.843 - 0.932	10.656	10.123 - 11.189	53.28	50.616 - 55.944	
	16	3	53	12	1.579	1.500 - 1.658	18.948	18.000 - 19.895	56.84	53.998 - 59.682	
	20	2	34	12	2.467	2.393 - 2.541	29.604	28.716 - 31.676	59.21	57.434 - 60.986	
	25	1	22	12	3.855	3.739 - 3.971	46.26	44.872 - 47.648	46.26	44.872 - 47.649	
1	32	1	13	12	6.316	6.127 - 6.506	75.792	73.518 - 78.066	75.79	73.516 - 78.064	

Physical and mechanical properties of Fe- 500 TMT bars as per IS- 1786 - 2008

PHYSICAL & MECHANICAL (MIN)					
0.2% P.S. (or Y.S) N/mm ² or MPA	500				
Tensile Strength N/mm2 or MPA	545				
Total Elongation % min	12				
CHEMICAL (MAX %)					
Carbon	0.25				
Sulphur	0.055				
Phosphorus	0.055				
Micro-Alloy	0.3				
Bend Test	No transverse crack should form after bending through 180° around a mandrel of dia specified below.				
Bars upto and including 20 mm, dia	4d				
Bars over 20 mm, dia	5d				
Rebend Test	No transverse crack should form after bending through 45° and reverse bending the same through 22.5° around the mandrel dia				
Bars upto and including 10 mm, dia	5d				
bars over 10 mm, dia	7d				







Assured quality



Unmatched service

































